

## Ultra-High Purity Dielectric Solvent Product Data Sheet

PO Box 9  
Tucker, GA 30085  
800-886-8240 • 770-621-8240  
[www.ecolink.com](http://www.ecolink.com)  
email: [info@ecolink.com](mailto:info@ecolink.com)

### Description

POSITRON embodies a series of important improvements over hydrocarbon/terpene blends previously used to replace 1, 1, 1 trichloroethane and CFC-113. POSITRON dries more rapidly and completely than any other terpene-based solvent available today. Thanks to the use of a patented distillation methodology, this material has very low odor.

POSITRON contains no oxidizers, and will not cause moisture condensation problems since it does not evaporate too rapidly. Unlike other electrical solvents, POSITRON is non-toxic, (see MSDS).

### Benefits

- Non-toxic
- Lower odor
- Faster dry-time
- More aggressive
- Ultra-low residue
- Safe & easy to use
- No hazardous fumes
- High dielectric strength, (ASTM D-877 test procedures to 48,000 volts.)
- No SARA or RCRA listed ingredients

### Applications

For use by customers seeking a high performance environmentally preferred alternative. POSITRON is used for a variety of electrical cleaning tasks. Use POSITRON in place of chlorinated solvents for all types of electrical and mechanical cleaning.

Use undiluted. Spray or wipe POSITRON on surface to be cleaned; oil dirt and carbon will flow off surface. If additional cleaning is desired, wipe with rag or brush.

### Key Physical Characteristics

<u>Property</u>	<u>Typical Value</u>
Boiling Point	348° F
Color	Clear, Colorless Liquid
Flash Point, Tag Closed Cup	142° F
Odor	Mild terpene
Solubility in Water	Negligible
Specific Gravity (H <sub>2</sub> O=1)	0.807 @ 25° C
Vapor Pressure (mm Hg)	.52 mm Hg @ 20° C
VOC Content	803 gm/liter

### Safety and Handling Precautions

Use with adequate ventilation. If vapor mist is generated, use a NIOSH certified organic vapor respirator with a dust and mist filter. Nitrile gloves and Safety glasses are recommended. Treat as combustible liquid. All rags used in conjunction with this product must be placed in a metal sealable container after use to avoid possible spontaneous combustion. Keep container closed. Avoid excessive contact with fumes or liquid. Refer to label and MSDS before use.

### Packaging

<u>Product Name</u>	<u>Part No.</u>	<u>Packaging</u>	<u>National Stock No.</u>
Positron	060-55	55 Gal Drum	6850-01-412-0028
Positron	060-6	6 Gal Pail	6850-01-412-0026
Positron	060-5	5 Gal Pail	
Positron	060-1	4 x 1 Gal Case	6850-01-411-8815
Positron-22	226-1	12 x 22 oz Pump Spray	6850-01-445-3541
Positron (A)	696-1	12 x 16 oz net Aerosol	6850-01-445-3545