

# TITAN<sup>®</sup>

## FIRE PROTECTION

# ABC

## Dry Chemical Wheeled Unit

**ECONOMICAL**

**RECHARGEABLE**

**CARBON STEEL CYLINDER**

**EPOXY POWDER COATED FINISH**

**ALL METAL COMPONENTS**

**TEMPERATURE RANGE -30°C to 60°C**

**TITAN ABC Dry Chemical Stored and External Pressured Wheeled Units** are manufactured to provide protection for hazardous areas where the potential for large fires exists. They can be strategically located to provide maximum protection for a wide variety of hazards, while taking up minimal space, and requiring only one trained person for operation.

This wheeled extinguisher is completely self-contained. Comes either Stored Pressured or attached with a CO<sub>2</sub> cylinder (external pressure), this is the only pressure source required to completely expel the fire extinguishing agent.

Some typical application include paint spray booths, dip tanks, offshore platforms, loading docks, fuel storage areas, airports and heavy manufacturing operations.



CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
<b>A</b>	Wood, paper, cloth, trash & other ordinary materials.	
<b>B</b>	Gasoline, oil, paint and other flammable liquids.	
<b>C</b>	May be used on fires involving live electrical equipment without danger to the operator.	

SPECIFICATIONS	STORED PRESSURE	EXTERNAL PRESSURE	
SIZE & CAPACITY KG. (LBS.)	25 (50)	50 (100)	125 (250)
CYLINDER LENGTH (MM.)	625	875	1100
CYLINDER WEIGHT (KG.)	11	32	50
RANGE (FT.)	35-40	35-40	35-40
EXTINGUISHER WEIGHT (KG.)	56	100	180
FILLED WEIGHT (KG.)	25	50	100

**APPROVALS: CE, EN3, ISO 9001**



MANUFACTURED TO EXACTING STANDARDS UNDER

**ISO 9001**  
QUALITY ASSURANCE



Complies with  
**BS EN3**

DISTRIBUTED BY:

**InterChem**

**INTERCHEM LIMITED**

♦ 9th Avenue South, Barataria, Trinidad.

♦ Tel.: (868) 638-3800

♦ Fax: (868) 638-3801

♦ Email: mail@interchem.co.tt

♦ Website: www.interchem.co.tt, www.titan.co.tt

**ABC DRY CHEMICAL WHEELED UNIT**