

# TITAN<sup>®</sup>

## FIRE PROTECTION

# CARBON DIOXIDE

**ECONOMICAL**

**RECHARGEABLE**

**ALUMINIUM ALLOY CYLINDER**

**STAINLESS STEEL HEAD ASSEMBLY**

**EPOXY POWDER COATED FINISH**

**ALL METAL COMPONENTS**

**5 YEAR WARRANTY**

**TEMPERATURE RANGE -30°C to 60°C**



AVAILABLE IN WHEELED AND STATIONARY MODELS.

### TITAN CARBON DIOXIDE

**Portable Fire Extinguishers** smother Class B and Class C fires quickly by displacing the oxygen in the air.

They are ideal for electronic and electrical rooms where other agents may cause further damage to equipment.

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
<b>B</b>	Gasoline, oil, paint and other flammable liquids.	
<b>C</b>	May be used on fires involving live electrical equipment without danger to the operator.	

SPECIFICATIONS	CARBON DIOXIDE			
SIZE & CAPACITY (LBS.)	5	10	15	20
APPLICATION	HORN	HOSE & HORN	HOSE & HORN	HOSE & HORN
MODEL NUMBER	PSE 0303	PSE 0306	PSE 0680	PSE 0900
CE RATING	34B	70B	100B	113B
WEIGHT (LBS.)	13.25	28	38	50
HEIGHT (IN.)	17	21	27.5	27.5
OUTER DIAMETER (IN.)	5.5	6	7	8
DISCHARGE TIME (SEC.)	10	10	12.5	19
STANDARD WALL BRACKET	YES	YES	YES	YES

**APPROVALS: CE, EN3, ISO 9001**

MANUFACTURED TO EXACTING STANDARDS UNDER



**ISO 9001**  
QUALITY ASSURANCE



Complies with **BS EN3**

DISTRIBUTED BY:

**InterChem**

**INTERCHEM LIMITED**

♦ 9th Avenue South, Barataria, Trinidad.

♦ Tel.: (868) 638-3800

♦ Fax: (868) 638-3801

♦ Email: mail@interchem.co.tt

♦ Website: www.interchem.co.tt, www.titan.co.tt

**CARBON DIOXIDE**