

TITAN[®]

FIRE PROTECTION

FOAM

ECONOMICAL

RECHARGEABLE

STORED PRESSURE DESIGN

STAINLESS STEEL CYLINDER

CORROSION RESISTANT SS304 ALLOY

STAINLESS STEEL HEAD ASSEMBLY

ALL METAL COMPONENTS

5 YEAR WARRANTY



TEMPERATURE RANGE -0°C to 60°C

BRACKETS OR HOOKS INCLUDED WITH ALL MODELS



TITAN FOAM Portable Fire Extinguishers use a AFFF foam at 3% solution. The AFFF formula provides a blanketing effect that smothers and cools both Class A & B fires, and greatly reduces flashback as it suppresses all vapours.

AVAILABLE IN WHEELED AND STATIONARY MODELS.

| CLASSES OF FIRES | TYPES OF FIRES | PICTURE SYMBOL |
|------------------|---|---|
| A | Wood, paper, cloth, trash & other ordinary materials. |  |
| B | Gasoline, oil, paint and other flammable liquids. |  |

| SPECIFICATIONS | AFFF FOAM | |
|-----------------------|--------------------|--------------------|
| SIZE & CAPACITY | 6 LITRE (1.6 gal.) | 9 LITRE (2.5 gal.) |
| APPLICATION | HOSE & NOZZLE | HOSE & NOZZLE |
| MODEL NUMBER | PSE22-01 | PSE22-09 |
| CE RATING | 27A 144B | 27A 144B |
| WEIGHT (LBS.) | 21 | 28 |
| HEIGHT (IN.) | 20 | 25 |
| OUTER DIAMETER (IN.) | 8 | 8 |
| DISCHARGE TIME (SEC.) | 60 | 60 |
| STANDARD WALL BRACKET | YES | YES |

APPROVALS: CE, EN3, ISO 9001

MANUFACTURED TO EXACTING STANDARDS UNDER



Complies with **BS EN3**

DISTRIBUTED BY:



INTERCHEM LIMITED

♦ 9th Avenue South, Barataria, Trinidad.

♦ Tel.: (868) 638-3800

♦ Fax: (868) 638-3801

♦ Email: mail@interchem.co.tt

♦ Website: www.interchem.co.tt, www.titan.co.tt

FOAM