

# TITAN<sup>®</sup>

## FIRE PROTECTION

# FOAM Wheeled Unit

**ECONOMICALLY PRICED**

**RECHARGEABLE**

**STORED PRESSURE DESIGN**



**EPOXY POWDER COATED FINISH**

**ALL METAL COMPONENTS**

**5 YEAR WARRANTY**

**TEMPERATURE RANGE -0°C to 55°C**

**MANUFACTURED OF DURABLE HIGH QUALITY MATERIALS**

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
<b>A</b>	Wood, paper, cloth, trash & other ordinary materials.	
<b>B</b>	Gasoline, oil, paint and other flammable liquids.	



TITAN FOAM Wheeled Fire Extinguishers use AFFF foam at 3% solution. The AFFF formula provides a blanketing effect that smothers and cools both Class A & B fires, and greatly reduces flashback as it suppresses all vapours.

SPECIFICATIONS	FOAM WHEELED UNITS
CAPACITY	50
CYLINDER LENGTH (MM.)	875
CYLINDER WEIGHT (KG.)	32
EXTINGUISHER WEIGHT (KG.)	100
FILLED WEIGHT (KG.)	50
OUTER DIAMETER (MM.)	320
VOLUME (L.)	59
TEMPERATURE RANGE	-0°C - 55°C
WORKING PRESSURE (BAR)	0
TEST PRESSURE (BAR)	35
MIN WALL-THICKNESS (MM.)	3.0
FIRE CLASS	55A IIB

**APPROVALS: CE, EN3, ISO 9001**

MANUFACTURED TO EXACTING STANDARDS UNDER



**ISO 9001**  
QUALITY ASSURANCE



Complies with  
**BS EN3**

DISTRIBUTED BY:

**InterChem**

**INTERCHEM LIMITED**

- ♦ 9th Avenue South, Barataria, Trinidad.
- ♦ Tel.: (868) 638-3800
- ♦ Fax: (868) 638-3801
- ♦ Email: mail@interchem.co.tt
- ♦ Website: www.interchem.co.tt, www.titan.co.tt

**FOAM WHEELED UNIT**