

SWING HOSE REEL

- ECONOMICAL**
- SIMPLE & COMPACT**
- EASY TO INSTALL**
- EPOXY POWDER COATED FINISH**
- METAL COMPONENTS**



TITAN Swing Hose Reel

Method of Operation

- ◆ Swing out hose reel in the required direction, manually turn on water supply and run out hose.
- ◆ Open jet spray nozzle.
- ◆ Aim at base of fire.
- ◆ Keep hose pressured when reeling back in.

SPECIFICATIONS	SWING HOSE REEL
HOSE SIZE	1"
MODEL NUMBER	PT01-25
HOSE	100 ft. EN694 Black P.V.C.
NOZZLE	PLASTIC JET/SPRAY
DRUM DEPTH (IN)	7 1/2"
DRUM DIAMETER (IN)	21 3/4"
COMPONENTS	INPUT TUBE - BRASS SPOKE/ROCKER ARM /MOUNTED PARTS/NOZZLE
WORKING PRESSURE	12 BAR / 175 P.S.I.
FINISH	RED EPOXY POWDERCOAT

APPROVALS: CE, EN671, EN694, ISO 9001



SWING HOSE REEL



Complies with
BS EN671
BS EN694

DISTRIBUTED BY:

InterChem

INTERCHEM LIMITED
 ◆ 9th Avenue South, Barataria, Trinidad.
 ◆ Tel.: (868) 638-3800
 ◆ Fax: (868) 638-3801
 ◆ Email: mail@interchem.co.tt
 ◆ Website: www.interchem.co.tt, www.titan.co.tt