

PROTECTIVE COATING

ELECTRO-SHIELD

F E A T U R E S

- Protective Dielectric seal
- Forms a flexible clear film
- Permanent rubber coating
- Prevents corrosion and rust
- Can be applied on electrical connections and joints
- Waterproof coating
- Non-chlorinated
- Dries in minutes

P R O P E R T I E S

Appearance: Clear coating when dry. Liquid has characteristic solvent odor

Boiling point: Not Evaluated

Specific gravity: 0.75-0.85 gr/cc

Non volatiles: 10 %

Solubility in water: Insoluble

Flash point: -134 to -130 °F

Storage stability: Keep away from direct sun light and open flames

Flammability: Flammable Aerosol

Packaging: 12x11oz Net Wt. Cans/Case

- Properties are typical and subject to usual manufacturing tolerances.

ELECTRO-SHIELD is a spray that forms a protective Dielectric Seal on electrical connections and other parts, preventing moisture and protecting against rust and corrosion. ELECTRO-SHIELD can be applied wherever a waterproof, flexible, permanent rubber film is needed. It dries in minutes to a clear film, allowing code colors or number pads to be seen. It also acts as a barrier to salt, mold and other environmental chemicals.

Shake can well before use and apply to clean dry surface holding can 6 to 8 inches from object. Spray in short even strokes until thoroughly coated. Let dry for 15 minutes before use. Clean up or remove excess with paint thinner. Do not apply to live high voltage connections or running electrical motors. Not intended for use under direct sunlight.

Refer to the attached MSDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by Interchem.

Distributed By:

Interchem Limited

Tel: (868) 638-3800

Fax: (868) 638-3801

www.interchem.co.tt